

Jamicon Series : CH

Teapo Series : DV

Wide temperature range ,long life Series

■ Endurance:105°C, 2000 hours

■ Recommended Applications: Suitable for AV(TV,Video,Audio),Monitor/Computer, Home appliance, OA/HA/Communication,Industrial, Automobile, Meter.

■ Corresponding product to RoHS





Jamicon


Teapo

■ Specifications

Item	Characteristics									
Category Temperature Range	-55 ~ +105°C						-25 ~ +105°C			
Rated Voltage Range	6.3 ~100VDC						160~450VDV			
Rated Capacitance Range	1~ 2200 μF									
Capacitance Tolerance	± 20 % (120Hz , 20°C)									
Leakage Current (20°C)	4~10Φ		12.5~16Φ			8~16Φ				
	I≤0.01CV or 3(μA),whichever is greater.		I≤0.03CV or 4(μA),whichever is greater.			I≤0.04CV+100 uA				
	(After rated voltage applied for 2 minutes)						(After rated voltage applied for 5 minutes)			
I= Leakage Current (μ A) C= Nominal Capacitance (μ F) V= Rated Voltage (V)										
Dissipation Factor(MAX) (tan δ) (120Hz ,20°C)	Shown in the table of standard ratings									
Low Temperature Stability Impedance Ratio (MAX)	WV Z(120HZ)	6.3	10	16	25	35~100	160~450			
	Z(-25°C) / Z(20°C)	4	3	2	2	2	4			
	Z(-40°C) / Z(20°C)	8	6	4	4	3	—			
Endurance	After applying rated voltage for 2000hrs at 105°C,Stay back to 20 °C temperature measurement,the capacitors shall meet the following requirements.									
	Case (Φ)	4~6.3Φ			8~16Φ					
	Capacitance Change	Within ±25% of the initial value			Within ±20% of the initial value					
	Dissipation Factor	Not more than 200% of the specified value								
	Leakage Current	Not more than the specified value								
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to item 4.1 of JIS C 5101-4.									

■ MARKING


Teapo




Jamicon

■ Dimensions

●General structure



●Vibration resistant structure



Dimensions	ΦD	L	A	H	W	P	K
B01	4.0	5.4	4.3	5.5 Max	0.65±0.1	1.0	0.35+0.15/-0.2
C01	5.0	5.4	5.3	6.5 Max	0.65±0.1	1.5	0.35+0.15/-0.2
E01	6.3	5.4	6.6	7.8 Max	0.65±0.1	2.1	0.35+0.15/-0.2
E04	6.3	7.7	6.6	7.8 Max	0.65±0.1	2.1	0.35+0.15/-0.2
G02	8.0	6.2	8.3	9.5 Max	0.65±0.1	2.2	0.35+0.15/-0.2
G03	8.0	10.2	8.3	10.0 Max	0.90±0.2	3.1	0.70±0.20
H03	10.0	10.2	10.3	12.0 Max	0.90±0.2	4.6	0.70±0.20
K05	12.5	13.5	13.0	15.0 Max	1.20±0.2	4.4	0.70±0.30
K06	12.5	16	13.0	15.0 Max	1.20±0.2	4.4	0.70±0.30
M06	16.0	16.5	17.0	19.0 Max	1.20±0.2	6.4	0.70±0.30

■ Multiplier for Ripple Current

Frequency (Hz)	60	120	1K	10K
Coefficient	0.85	1.00	1.15	1.25

Jamicon Series : CH

Teapo Series : DV

STANDARD RATINGS

Rated Voltage (SurageVoltage) (V)	Cap (μ F)	Case size Φ DxL(mm)	$\tan \delta$	Ripple current (mA/rms 105°C) (120Hz)	Rated Voltage (SurageVoltage) (V)	Cap (μ F)	Case size Φ DxL(mm)	$\tan \delta$	Ripple current (mA/rms 105°C) (120Hz)
6.3(8)	22	4x5.4	0.30	26	25(32)	47	6.3x7.7	0.14	91
	33	4x5.4	0.30	29		6.3x7.7	0.14	100	
	47	4x5.4	0.30	31		100	8x6.2	0.16	100
		5x5.4	0.30	46		8x10.2	0.16	230	
	100	5x5.4	0.30	47		220	8x10.2	0.16	270
		6.3x5.4	0.30	71		330	10x10.2	0.16	310
		6.3x5.4	0.30	80		470	10x10.2	0.16	380
	220	6.3x7.7	0.30	120		1000	12.5x13.5	0.26	510
		6.3x7.7	0.30	140		1500	12.5x16	0.26	590
	330	8x6.2	0.35	140		2200	16x16.5	0.26	900
		8x10.2	0.35	290		4.7	4x5.4	0.12	22
		8x10.2	0.35	380		6.8	4x5.4	0.12	25
	470	10x10.2	0.35	290		10	5x5.4	0.12	30
		10x10.2	0.35	410		22	5x5.4	0.12	35
		1500	0.35	460		6.3x5.4	0.12	60	
	2200	12.5x13.5	0.35	680	35(44)	4.7	6.3x7.7	0.12	80
10(13)	10	4x5.4	0.22	20		6.3x7.7	0.12	80	
	22	4x5.4	0.22	23		8x6.2	0.12	80	
	33	4x5.4	0.22	26		6.3x5.4	0.12	60	
		5x5.4	0.22	45		47	6.3x7.7	0.12	100
	47	5x5.4	0.22	60		8x10.2	0.14	210	
		6.3x5.4	0.22	70		6.3x7.7	0.12	105	
		5x5.4	0.22	60		100	8x10.2	0.14	240
	100	6.3x5.4	0.22	75		10x10.2	0.14	310	
		6.3x7.7	0.22	110		12.5x13.5	0.14	390	
		6.3x7.7	0.22	120		220	8x10.2	0.14	260
	220	8x6.2	0.26	120		10x10.2	0.14	350	
		8x10.2	0.26	260		330	10x10.2	0.14	370
		6.3x7.7	0.26	200		470	12.5x13.5	0.22	520
	330	8x10.2	0.26	290		680	12.5x13.5	0.22	590
		8x10.2	0.26	320		1000	16x16.5	0.22	800
		10x10.2	0.26	380		1500	16x16.5	0.22	1000
	680	8x10.2	0.26	360	50(63)	1	4x5.4	0.12	10
	1000	10x10.2	0.26	410		2.2	4x5.4	0.12	16
	2200	12.5x13.5	0.26	680		3.3	4x5.4	0.12	16
16(20)	10	4x5.4	0.16	28		4.7	5x5.4	0.12	23
	22	4x5.4	0.16	29		6.8	5x5.4	0.12	30
	5x5.4	0.16	39	10	5x5.4	0.12	35		
	33	5x5.4	0.16		40	6.3x5.4	0.12	40	
	47	5x5.4	0.16		42	22	6.3x5.4	0.12	42
		6.3x5.4	0.16		70	6.3x7.7	0.12	65	
	100	6.3x5.4	0.16		71	33	6.3x7.7	0.12	91
		6.3x7.7	0.16		130	8x6.2	0.12	110	
	220	6.3x7.7	0.16		130	6.3x7.7	0.12	110	
		8x6.2	0.20		130	47	8x6.2	0.12	110
		8x10.2	0.20		150	8x10.2	0.12	210	
		10x10.2	0.20		210	100	8x10.2	0.12	240
	330	10x10.2	0.20		260	10x10.2	0.12	320	
	470	8x10.2	0.20		240	150	10x10.2	0.12	300
		10x10.2	0.20		380	220	10x10.2	0.12	330
	1000	12.5x13.5	0.34		550	330	12.5x13.5	0.16	490
	2200	16x16.5	0.34		900	470	12.5x16	0.18	550
25(32)	3.3	4x5.4	0.14		18	1000	16x16.5	0.18	800
	4.7	4x5.4	0.14	22	63(79)	33	8x10.2	0.18	140
	6.8	4x5.4	0.14	25		47	8x10.2	0.18	170
	10	4x5.4	0.14	25		100	10x10.2	0.18	340
		5x5.4	0.14	28		150	10x10.2	0.18	360
	22	5x5.4	0.14	28		220	12.5x13.5	0.14	470
		6.3x5.4	0.14	55		220	12.5x16	0.14	550
	33	6.3x5.4	0.14	65		330	16x16.5	0.14	650
	47	6.3x5.4	0.14	65		470	16x16.5	0.14	700

Jamicon Series : CH

Teapo Series : DV

STANDARD RATINGS

Rated Voltage (SurageVoltage) (V)	Cap (μ F)	Case size Φ DxL(mm)	$\tan \delta$ (%)	Ripple current (mA/rms 105°C) (120Hz)
100(125)	10	6.3x7.7	0.18	50
	22	8x10.2	0.18	100
	33	8x10.2	0.18	120
		10x10.2	0.18	150
	47	10x10.2	0.18	170
		12.5x13.5	0.18	250
160(200)	100	12.5x13.5	0.18	300
	33	12.5x13.5	0.20	95
	47	16x16.5	0.20	240
	100	16x16.5	0.20	250
200(250)	10	12.5x13.5	0.20	80
	22	12.5x16	0.20	110
	33	12.5x16	0.20	120
	47	16x16.5	0.20	220

Rated Voltage (SurageVoltage) (V)	Cap (μ F)	Case size Φ DxL(mm)	$\tan \delta$ (%)	Ripple current (mA/rms 105°C) (120Hz)
250(300)	3.3	12.5x13.5	0.20	60
	4.7	12.5x13.5	0.20	65
	10	12.5x13.5	0.20	70
		22	12.5x13.5	0.20
	33	16x16.5	0.20	180
	47	16x16.5	0.20	220
400 (450)	3.3	12.5x13.5	0.25	40
	4.7	12.5x13.5	0.25	45
	10	12.5x13.5	0.25	50
		22	16x16.5	0.25
	33	16x16.5	0.25	85
	47	12.5x13.5	0.25	40
450 (500)	4.7	12.5x13.5	0.25	45
	10	12.5x16	0.25	75
		22	16x16.5	0.25
	22	12.5x13.5	0.25	85