

SRPASSIVES

Multilayer Ceramic Capacitor (Radial Leads)



Rated Voltage: 50V

Pitch 5.08mm

Part number	Capacitance [F]	Dielectric	Tolerance [%]	Operating temp. range [°C]
CM-10	10p	NP0	±5	-55...125
CM-22	22p	NP0	±5	-55...125
CM-33	33p	NP0	±5	-55...125
CM-47	47p	NP0	±5	-55...125
CM-68	68p	NP0	±5	-55...125
CM-100	100p	NP0	±5	-55...125
CM-150	150p	NP0	±5	-55...125
CM-220	220p	NP0	±5	-55...125
CM-330	330p	NP0	±5	-55...125
CM-470	470p	X7R	±10	-55...125
CM-680	680p	X7R	±10	-55...125
CM-1N	1n	X7R	±10	-55...125
CM-1.5N	1n5	X7R	±10	-55...125
CM-2.2N	2n2	X7R	±10	-55...125
CM-3.3N	3n3	X7R	±10	-55...125
CM-4.7N	4n7	X7R	±10	-55...125
CM-10N	10n	X7R	±10	-55...125
CM-15N	15n	X7R	±10	-55...125
CM-22N	22n	X7R	±10	-55...125
CM-33N	33n	Z5U	±20	10...85
CM-47N	47n	Z5U	±20	10...85
CM-47N-Y5V	47n	Y5V	-82...+22	-30...85
CM-68N	68n	Z5U	±20	10...85
CM-100N	100n	Z5U	±20	10...85
CM-100N-X7R	100n	X7R	±10	-55...125
CM-100N-X7R-T	100n	X7R	±10	-55...125

CM-100N-Y5V	100n	Y5V	-80...+22	-30...85
CM-150N	150n	Z5U	±20	10...85
CM-220N	220n	Z5U	±20	10...85
CM-220N-Y5V	220n	Y5V	-80...+22	-30...85
CM-330N	330n	Z5U	±20	10...85
CM-470N	470n	Z5U	±20	10...85
CM-470N-Y5V	470n	Y5V	-82...+22	-30...85
CM-680N	680n	Z5U	±20	10...85
CM-1U	1u	Z5U	±20	10...85
CM-1U-Y5V	1u	Y5V	-80...+22	-30...85

Pitch 2.54mm

Part number	Capacitance [F]	Dielectric	Tolerance [%]	Operating temp. range [°C]
CM-22/S	22p	NP0	±5	-55...125
CM-27/S	27p	NP0	±5	-55...125
CM-33/S	33p	NP0	±5	-55...125
CM-47/S	47p	NP0	±5	-55...125
CM-100/S	100p	NP0	±5	-55...125
CM-120/S	120p	NP0	±5	-55...125
CM-470/S	470p	NP0	±5	-55...125
CM-1N/S	1n	X7R	±10	-55...125
CM-10N/S	10n	X7R	±10	-55...125
CM-22N/S	22n	X7R	±10	-55...125
CM-47N/S	47n	X7R	±10	-55...125
CM-100N/S	100n	X7R	±10	-55...125