



Non-Insulated Cord End Terminal						
Max voltage : 150°C Ui=300V				Material : Copper		
ITEM NO	Dimension (mm)				Cable Size	
	L	D	C	W	mm²	A.W.G.
EN0206	6.0	1.0	0.7	1.4	0.2	26
EN0207	7.0	1.0	0.7	1.4	0.2	26
EN0208	8.0	1.0	0.7	1.4	0.2	26
EN0306	6.0	1.1	0.8	1.5	0.3	24
EN0308	8.0	1.1	0.8	1.5	0.3	24
EN0506	6.0	1.3	1.0	1.7	0.5	22
EN0508	8.0	1.3	1.0	1.7	0.5	22
EN0510	10.0	1.3	1.0	1.7	0.5	22
EN0512	12.0	1.3	1.0	1.7	0.5	22
EN7506	6.0	1.6	1.3	1.9	0.8	20
EN7508	8.0	1.6	1.3	1.9	0.8	20
EN7510	10.0	1.6	1.3	1.9	0.8	20
EN7512	12.0	1.6	1.3	1.9	0.8	20
EN1006	6.0	1.8	1.5	2.2	1.0	18
EN1008	8.0	1.8	1.5	2.2	1.0	18
EN1010	10.0	1.8	1.5	2.2	1.0	18
EN1012	12.0	1.8	1.5	2.2	1.0	18
EN1507	7.0	2.0	1.8	2.5	1.5	16
EN1508	8.0	2.0	1.8	2.5	1.5	16
EN1512	12.0	2.0	1.8	2.5	1.5	16
EN1518	18.0	2.0	1.8	2.5	1.5	16
EN2507	7.0	2.6	2.3	3.3	2.5	14
EN2508	8.0	2.6	2.3	3.3	2.5	14
EN2510	10.0	2.6	2.3	3.3	2.5	14
EN2512	12.0	2.6	2.3	3.3	2.5	14
EN2518	18.0	2.6	2.3	3.3	2.5	14
EN4009	9.0	3.2	2.8	3.9	4.0	12
EN4012	12.0	3.2	2.8	3.9	4.0	12
EN4018	18.0	3.2	2.8	3.9	4.0	12
EN6010	10.0	3.9	3.5	4.8	6.0	10
EN6012	12.0	3.9	3.5	4.8	6.0	10
EN6015	15.0	3.9	3.5	4.8	6.0	10
EN6018	18.0	3.9	3.5	4.8	6.0	10
EN10-12	12.0	4.9	4.5	5.8	10.0	7
EN10-15	15.0	4.9	4.5	5.8	10.0	7
EN10-18	18.0	4.9	4.5	5.8	10.0	7
EN16-12	12.0	6.2	5.8	7.2	16.0	5
EN16-15	15.0	6.2	5.8	7.2	16.0	5
EN16-18	18.0	6.2	5.8	7.2	16.0	5
EN25-16	16.0	7.9	7.5	9.1	25.0	4
EN25-22	22.0	7.9	7.5	9.1	25.0	4
EN35-16	16.0	8.7	8.3	10.2	35.0	2
EN35-25	25.0	8.7	8.3	10.2	35.0	2
EN50-20	20.0	10.9	10.3	12.4	50.0	1
EN50-25	25.0	10.9	10.3	12.4	50.0	1
EN50-30	30.0	10.9	10.3	12.7	50.0	1/0
EN50-32	32.0	10.9	10.3	12.7	50.0	1/0