



**NYLON-INSULATED  
CORD END TERMINALS  
(E SERIES)**











**MAXIMUM ELECTRIC CURRENT:**

A.W.G.	26	24	22	20	18	16	14	12	10	8	6	4	2	1/0	2/0	3/0	4/0	250	300
AMP.	5.5	7	9	12	17	18	30	35	50	70	95	125	170	230	265	310	360	405	445

**MAXIMUM ELECTRICAL RATING:** 105°C 600 VOLTS MAX.

**CONNECTOR MATERIAL:** COPPER TUBE.

**INSULATION MATERIAL:** NYLON

WIRE RANGE A.W.G. mm <sup>2</sup>	ITEM NO.	DIMENSION inch(mm)						FRENCH COLOR	GERMAN COLOR	DIN COLOR
		F	L	W	B	D	C			
26 A.W.G. 0.25 mm <sup>2</sup>	E0206	0.236 6	0.409 10.4	0.075 1.9	0.173 4.4	0.043 1.100	0.031 0.8	VIOLET	LIGHT_BLUE	
	E0208	0.315 8	0.488 12.4	0.075 1.9	0.173 4.4	0.043 1.100	0.031 0.8			
24 A.W.G. 0.34 mm <sup>2</sup>	E0306	0.236 6	0.409 10.4	0.075 1.9	0.173 4.4	0.043 1.100	0.031 0.8	PINK	TURQUOISE	
	E0308	0.315 8	0.488 12.4	0.075 1.9	0.173 4.4	0.043 1.100	0.031 0.8			
22 A.W.G. 0.5 mm <sup>2</sup>	E0505	0.197 5	0.433 11	0.102 2.6	0.236 6	0.051 1.300	0.039 1	WHITE	ORANGE	WHITE
	E0506	0.236 6	0.472 12	0.102 2.6	0.236 6	0.051 1.300	0.039 1			
	E0508	0.315 8	0.551 14	0.102 2.6	0.236 6	0.051 1.300	0.039 1			
	E0510	0.394 10	0.63 16	0.102 2.6	0.236 6	0.051 1.300	0.039 1			
	E0512	0.472 12	0.709 18	0.102 2.6	0.236 6	0.051 1.300	0.039 1			
20 A.W.G. 0.75 mm <sup>2</sup>	E7506	0.236 6	0.472 12	0.11 2.8	0.248 6.3	0.059 1.500	0.047 1.2	BLUE	WHITE	GREY
	E7508	0.315 8	0.551 14	0.11 2.8	0.248 6.3	0.059 1.500	0.047 1.2			
	E7508-L	0.315 8	0.571 14.5	0.118 3	0.256 6.5	0.059 1.500	0.047 1.2			
	E7510	0.394 10	0.63 160	0.11 2.8	0.26 6.3	0.059 1.500	0.047 1.2			
	E7512	0.472 12	0.709 18	0.11 2.8	0.26 6.3	0.059 1.500	0.047 1.2			
	E7518	0.709 18	0.957 24.3	0.11 2.8	0.26 6.3	0.059 1.500	0.047 1.2			

