


母全绝缘端头

VINYL FULLY INSULATED FEMALE DISCONNECTORS



■ Conductor section: 0.5~1.5mm²(A.W.G22~16) 1max=10A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)			
		B	D φ	d φ	L
FDFD 1.25-187(5)	0.5 × 4.75	5.6	3.8	1.7	20.8
FDFD 1.25-187(8)	0.8 × 4.75	5.6	3.8	1.7	20.8
FDFD 1.25-250	0.8 × 6.35	7.4	3.8	1.7	24.3

■ Conductor section: 1.5~2.5mm²(A.W.G16~14) 1max=15A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)			
		B	D φ	d φ	L
FDFD 2-187(5)	0.5 × 4.75	5.6	4.3	2.3	20.8
FDFD 2-187(8)	0.8 × 4.75	5.6	4.3	2.3	20.8
FDFD 2-250	0.8 × 6.35	7.4	4.3	2.3	24.3


■ Conductor section: 4~6mm²(A.W.G12~10) 1max=24A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)			
		B	D φ	d φ	L
FDFD 5.5-250	0.8 × 6.35	7.4	5.7	3.4	24.3



肩背形公母预绝缘端头

VINYL-INSULATED PIGGY-BACK DISCONNECTORS



■ Conductor section: 0.5~1.5mm²(A.W.G22~16) 1max=10A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)					
		B	B1	H	D φ	d φ	L
PBDD 1.25-250	0.8 × 6.35	7.4	6.3	10.6	3.8	1.7	21.0

■ Conductor section: 1.5~2.5mm²(A.W.G16~14) 1max=15A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)					
		B	B1	H	D φ	d φ	L
PBDD 2-250	0.8 × 6.35	7.7	6.3	10.6	4.3	2.3	21.0

■ Conductor section: 4~6mm²(A.W.G12~10) 1max=24A Material: Brass

ITEM NO.	Nema Tab (mm)	Dimension(mm)					
		B	B1	H	D φ	d φ	L
PBDD 5.5-250	0.8 × 6.35	7.7	6.3	13.5	5.7	3.4	23.5

