



PF MOTOR & FAN

PF8025A2MSL-7

2-wire fan without speed sensor

Technical parameters:

- Dimensions: 80 x 80 x 25 mm
- Power supply: 230VAC
- Air Flow: 28.9³/hr
- Current : 0.08A
- Speed: 2300rpm
- Noise level (at 1m): 30dB
- Weight: 230g
- Operating temperature: -20° C ~ +80° C

SUZHOU PF MOTOR & FAN

Model Numbering System

Example: PF 12038 A2 H B L -5
1 2 3 4 5 6 7

1. PF: PF MOTOR & FAN

2. FAN SIZE (Model List)

2510	25x25x10mm	7015	70x70x15mm	10025	100x100x25mm
3010	30x30x10mm	7020	70x70x20mm	11025	110x110x25mm
4010	40x40x10mm	7515	70x70x15mm	12025	120x120x25mm
4020	40x40x20mm	7025	70x70x25mm	12032	120x120x32mm
5010	50x50x10mm	7525	75x75x25mm	12038	120x120x38mm
5015	50x50x15mm	8015	80x80x15mm	13532	135x135x32mm
5020	50x50x20mm	8020	80x80x20mm	13538	135x135x38mm
6010	60x60x10mm	8025	80x80x25mm	15038	150x150x38mm
6015	60x60x15mm	8038	80x80x38mm	15050	150x150x50mm
6020	60x60x20mm	9225	92x92x25mm	17251	172x150x51mm
6025	60x60x25mm	9238	92x92x38mm	18060	180x180x60mm
6028	60x60x28mm	9733	97x97x33mm	22060	220x220x60mm

3. INPUT VOLTAGE

D5 5VDC	D24 24VDC	A24 24VAC	A2 220-240VAC	AB (Dual Voltage) 110/220VAC
D12 12VDC	D48 48VDC	A1 110-120VAC	A3 360-380VAC	E EC FAN

4. SPEED TYPE

L: Low Speed M: Middle Speed H: High Speed U: Ultra Speed

5. BEARING TYPE

B: Ball Bearing S: Sleeve Bearing

6. LEAD TYPE

L: Wire Lead T: Terminal

7. IMPELLER NUMBER

5: 5 Impeller 7: 7 Impeller