



Part No.	Emitting Colour + Material	Wave-length (nm)	Lens Type	Angle of half sensitivity	Dimensions Fig.-No.	Dimension
L-932P3C	Silicon	940	water clear	30°	7	
L-932P3BT	Silicon	940	blue-transparent	30°	7	
L-53P3C	Silicon	940	water clear	30°	11	
L-53P3BT	Silicon	940	blue-transparent	30°	11	

**Electrical and radiant characteristics (T=25°C)**

Symbol	Parameter	min	typ	max	Unit	Test Condition
$V_{BR\ CE0}$	Collector-to-Emitter Breakdown Voltage	30			V	$I_C=100\ \mu A$ $I_B=0$
$V_{BR\ EC0}$	Emitter-to-Collector Breakdown Voltage	5			V	$I_E=100\ \mu A$ $I_B=0$
$V_{CE\ (SAT)}$	Collector-to-Emitter Saturation Voltage			0,8	V	$I_C=0,1\ mA$ $H=2,5\ mW/cm^2$
$I_D$	Dark Current			100	nA	$V_{CE}=10\ V$ $H=0\ mW/cm^2$
$T_R$	Rise Time (10% to 90%)		3		$\mu s$	$V_{CE}=5\ V$ $I_C=1\ mA$
$T_F$	Fall Time (10% to 90%)		3		$\mu s$	$R_L=100\ ohms$
	On State Collector Current	1		2	mA	$V_{CE}=5\ V$ $I_{(ON)}$ $E_0=1\ mW/cm^2$ $\lambda=940\ nm$
		2		4	mA	
		4		8	mA	
		8			mA	

**Absolute maximum ratings**

(T=25°C)	Unit
Collector-to-Emitter Breakdown Voltage $V_{BR\ CE0}$	30V
Emitter-to-Collector Breakdown Voltage	5V
Operating Temperature Range	-40°C +85°C
Lead Soldering Temperature (1,6 mm from body for 5 sec .)	260 °C
Power Dissipation at (or below) 25°C Free Air Temperature	100 mW
Storage Temperature Range	-40°C +85°C