










Spacers

– special lengths on request

					
art. no.	dim. [mm] C	art. no.	dim. [mm] C	art. no.	dim. [mm] C
DR 071 V0	1	DR 079 V0	9	DR 725 V0	25
DR 072 V0	2	DR 710 V0	10	DR 730 V0	30
DR 073 V0	3	DR 711 V0	11	DR 735 V0	35
DR 074 V0	4	DR 712 V0	12	DR 740 V0	40
DR 075 V0	5	DR 713 V0	13	DR 745 V0	45
DR 076 V0	6	DR 714 V0	14	DR 750 V0	50
DR 077 V0	7	DR 715 V0	15	DR 760 V0	60
DR 078 V0	8	DR 720 V0	20		
					
art. no.	dim. [mm] C	art. no.	dim. [mm] C	art. no.	dim. [mm] C
DR 081 V0	1	DR 089 V0	9	DR 825 V0	25
DR 082 V0	2	DR 810 V0	10	DR 830 V0	30
DR 083 V0	3	DR 811 V0	11	DR 835 V0	35
DR 084 V0	4	DR 812 V0	12	DR 840 V0	40
DR 085 V0	5	DR 813 V0	13	DR 845 V0	45
DR 086 V0	6	DR 814 V0	14	DR 850 V0	50
DR 087 V0	7	DR 815 V0	15	DR 860 V0	60
DR 088 V0	8	DR 820 V0	20		
					
art. no.	dim. [mm] C	art. no.	dim. [mm] C	art. no.	dim. [mm] C
DR 105 V0	5	DR 125 V0	25	DR 145 V0	45
DR 110 V0	10	DR 130 V0	30	DR 150 V0	50
DR 115 V0	15	DR 135 V0	35		
DR 120 V0	20	DR 140 V0	40		
material:	polyamide				
heat distortion:	180°C				
temperature range:	+180°C				
colour:	black				
class of inflammability:	UL 94 V-0				