


2000 Slide Switches - Snap fit and panel mount 10A 250Vac



115/230 is preferred legend

- ▶ 2 way 'voltage selector'
- ▶ Ratings up to 16A, 250V ac
- ▶ Snap fit and panel mount
- ▶ PCB & solder terminals
- ▶ 2 and 3 position
- ▶ Choice of circuits
- ▶ Choice of actuators

Approvals and specifications



10 A 250Vac T85
6(3)A 250Vac T85



UL CSA 16A 250Vac Non Inductive
UL CSA 4A 300Vac
UL 65°C, file no. E45221, CSA file no. LR10990

μ contact gap

Please specify: Standard action (SP116) or light action (SP118).
2000 series lubrication is inorganic and does not degrade plastics.

Technical data on pages 4 & 5.

T 2 2 20 5 B ---

TERMINAL SERIES POSITIONS CIRCUIT SLIDER BODY PRINT, COLOUR, ETC

slide
switches

▶ TERMINAL	▶ SERIES	▶ POS'N	▶ CIRCUIT Viewed from back	▶ SLIDER				
K 2.8 x 0.8			10 20 30 40 	0 2 Pos B Body only 6 2 & 3 Pos B Body only 2 2 Pos B Body only 7 2 & 3 Pos B Body only 3 2 & 3 Pos B Body only 4 2 & 3 Pos B Body only 5 2 Pos B Body only Also with legend A 2 Pos B Body only K 2 & 3 Pos B Body only Limited travel on 2 pos R 2 & 3 Pos B Body only Limited travel on 2 pos 	C 2 & 3 Pos B Body only D 2 & 3 Pos B Body only E 2 Pos B Body only Limited travel on 2 pos H 2 Pos B Body only K 2 & 3 Pos B Body only Limited travel on 2 pos R 2 & 3 Pos B Body only Limited travel on 2 pos 	L 2 & 3 Pos B Body only Limited travel on 2 pos M F Body only Legend optional N 2 Pos B Body only P 2 & 3 Pos B Body only Limited travel on 2 pos R 2 & 3 Pos B Body only Limited travel on 2 pos 	S Limited travel on 2 pos 2 & 3 Pos B Body only T 2 & 3 Pos B Body only 	
R 2.8 x 0.8		2 Switching positions						
T Solder	2							
X PCB 0.8 Sq. For mounting stability switches have extra "support" terminals * Nominal - Dimension varies with body type. For exact figure call sales		3 Switching positions						



T22208E ---



T22308E ---



T2230MF ---



T22205B ---




T22305B ---




T23204B ---

BODY

B With mounting holes




E Snap fit



Cut-outs must be punched in the direction of insertion

F Snap fit (single pole ON OFF only)



Cut-outs must be punched in the direction of insertion

OPTIONS

Colour

For custom slider colours call sales. A full range is available for large orders

Standard body colour is black

Legend printing


A wide range is available

For all options call sales


DIMENSIONS (mm)

Cut-out / PCB Matrix



2 Pos B



3 Pos B



2 Pos E



2 Pos F

