


# TIC106 SERIES SILICON CONTROLLED RECTIFIERS

Copyright © 1997, Power Innovations Limited, UK

APRIL 1971 - REVISED MARCH 1997

- 5 A Continuous On-State Current
- 30 A Surge-Current
- Glass Passivated Wafer
- 400 V to 800 V Off-State Voltage
- Max  $I_{GT}$  of 200  $\mu$ A



Pin 2 is in electrical contact with the mounting base.

MDC1ACA

## absolute maximum ratings over operating case temperature (unless otherwise noted)

RATING		SYMBOL	VALUE	UNIT
Repetitive peak off-state voltage (see Note 1)	TIC106D	$V_{DRM}$	400	V
	TIC106M		600	
	TIC106S		700	
	TIC106N		800	
Repetitive peak reverse voltage	TIC106D	$V_{RRM}$	400	V
	TIC106M		600	
	TIC106S		700	
	TIC106N		800	
Continuous on-state current at (or below) 80°C case temperature (see Note 2)		$I_{T(RMS)}$	5	A
Average on-state current (180° conduction angle) at (or below) 80°C case temperature (see Note 3)		$I_{T(AV)}$	3.2	A
Surge on-state current (see Note 4)		$I_{TM}$	30	A
Peak positive gate current (pulse width $\leq$ 300 $\mu$ s)		$I_{GM}$	0.2	A
Peak gate power dissipation (pulse width $\leq$ 300 $\mu$ s)		$P_{GM}$	1.3	W
Average gate power dissipation (see Note 5)		$P_{G(AV)}$	0.3	W
Operating case temperature range		$T_C$	-40 to +110	°C
Storage temperature range		$T_{stg}$	-40 to +125	°C
Lead temperature 1.6 mm from case for 10 seconds		$T_L$	230	°C

- NOTES: 1. These values apply when the gate-cathode resistance  $R_{GK} = 1 \text{ k}\Omega$ .
2. These values apply for continuous dc operation with resistive load. Above 80°C derate linearly to zero at 110°C.
3. This value may be applied continuously under single phase 50 Hz half-sine-wave operation with resistive load. Above 80°C derate linearly to zero at 110°C.
4. This value applies for one 50 Hz half-sine-wave when the device is operating at (or below) the rated value of peak reverse voltage and on-state current. Surge may be repeated after the device has returned to original thermal equilibrium.
5. This value applies for a maximum averaging time of 20 ms.

## PRODUCT INFORMATION

Information is current as of publication date. Products conform to specifications in accordance with the terms of Power Innovations standard warranty. Production processing does not necessarily include testing of all parameters.



# TIC106 SERIES

## SILICON CONTROLLED RECTIFIERS

APRIL 1971 - REVISED MARCH 1997

### electrical characteristics at 25°C case temperature (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{DRM}$ Repetitive peak off-state current	$V_D = \text{rated } V_{DRM}$ $R_{GK} = 1 \text{ k}\Omega$ $T_C = 110^\circ\text{C}$			400	$\mu\text{A}$
$I_{RRM}$ Repetitive peak reverse current	$V_R = \text{rated } V_{RRM}$ $I_G = 0$ $T_C = 110^\circ\text{C}$			1	mA
$I_{GT}$ Gate trigger current	$V_{AA} = 6 \text{ V}$ $R_L = 100 \Omega$ $t_{p(g)} \geq 20 \mu\text{s}$		60	200	$\mu\text{A}$
$V_{GT}$ Gate trigger voltage	$V_{AA} = 6 \text{ V}$ $R_L = 100 \Omega$ $R_{GK} = 1 \text{ k}\Omega$ $t_{p(g)} \geq 20 \mu\text{s}$ $T_C = -40^\circ\text{C}$			1.2	V
	$V_{AA} = 6 \text{ V}$ $R_L = 100 \Omega$ $R_{GK} = 1 \text{ k}\Omega$ $t_{p(g)} \geq 20 \mu\text{s}$ $T_C = 110^\circ\text{C}$	0.4	0.6	1	
	$V_{AA} = 6 \text{ V}$ $R_L = 100 \Omega$ $R_{GK} = 1 \text{ k}\Omega$ $t_{p(g)} \geq 20 \mu\text{s}$ $T_C = 110^\circ\text{C}$	0.2			
$I_H$ Holding current	$V_{AA} = 6 \text{ V}$ $R_{GK} = 1 \text{ k}\Omega$ $T_C = -40^\circ\text{C}$ Initiating $I_T = 10 \text{ mA}$			8	mA
	$V_{AA} = 6 \text{ V}$ $R_{GK} = 1 \text{ k}\Omega$ Initiating $I_T = 10 \text{ mA}$			5	
$V_{TM}$ Peak on-state voltage	$I_{TM} = 5 \text{ A}$ (See Note 6)			1.7	V
dv/dt Critical rate of rise of off-state voltage	$V_D = \text{rated } V_D$ $R_{GK} = 1 \text{ k}\Omega$ $T_C = 110^\circ\text{C}$		10		V/ $\mu\text{s}$

NOTE 6: This parameter must be measured using pulse techniques,  $t_p = 300 \mu\text{s}$ , duty cycle  $\leq 2\%$ . Voltage sensing-contacts, separate from the current carrying contacts, are located within 3.2 mm from the device body.

### thermal characteristics

PARAMETER	MIN	TYP	MAX	UNIT
$R_{\theta JC}$ Junction to case thermal resistance			3.5	$^\circ\text{C/W}$
$R_{\theta JA}$ Junction to free air thermal resistance			62.5	$^\circ\text{C/W}$

### resistive-load-switching characteristics at 25°C case temperature

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$t_{gt}$ Gate-controlled turn-on time	$I_T = 5 \text{ A}$ $I_G = 10 \text{ mA}$ See Figure 1		1.75		$\mu\text{s}$
$t_q$ Circuit-commutated turn-off time	$I_T = 5 \text{ A}$ $I_G = 10 \text{ mA}$ $I_{RM} = 8 \text{ A}$ See Figure 2		7.7		$\mu\text{s}$

## PRODUCT INFORMATION

## PARAMETER MEASUREMENT INFORMATION





Figure 1. Gate-controlled turn-on time



- NOTES:
- A. Resistor R1 is adjusted for the specified value of  $I_{RM}$ .
  - B. Resistor R2 value is  $30/I_H$ , where  $I_H$  is the holding current value of thyristor TH1.
  - C. Thyristor TH1 is the same device type as the DUT.
  - D. Pulse Generators, G1 and G2, are synchronised to produce an on-state anode current waveform with the following characteristics:
    - $t_p = 50 \mu s$  to  $300 \mu s$
    - duty cycle = 1%
  - E. Pulse Generators, G1 and G2, have output pulse amplitude,  $V_G$ , of  $\geq 20 V$  and duration of  $10 \mu s$  to  $20 \mu s$ .

Figure 2. Circuit-commutated turn-off time

# TIC106 SERIES SILICON CONTROLLED RECTIFIERS

APRIL 1971 - REVISED MARCH 1997

## TYPICAL CHARACTERISTICS

**AVERAGE ANODE ON-STATE CURRENT  
DERATING CURVE**




Figure 3.

**MAX CONTINUOUS ANODE POWER DISSIPATED  
vs  
CONTINUOUS ON-STATE CURRENT**




Figure 4.

**SURGE ON-STATE CURRENT  
vs  
CYCLES OF CURRENT DURATION**




Figure 5.

**TRANSIENT THERMAL RESISTANCE  
vs  
CYCLES OF CURRENT DURATION**




Figure 6.

## PRODUCT INFORMATION

**TYPICAL CHARACTERISTICS**




Figure 7.




Figure 8.




Figure 9.




Figure 10.

# TIC106 SERIES SILICON CONTROLLED RECTIFIERS

APRIL 1971 - REVISED MARCH 1997

## TYPICAL CHARACTERISTICS




Figure 11.




Figure 12.

**CIRCUIT-COMMUTATED TURN-OFF TIME  
vs  
CASE TEMPERATURE**




Figure 13.

## PRODUCT INFORMATION


# TIC106 SERIES SILICON CONTROLLED RECTIFIERS

APRIL 1971 - REVISED MARCH 1997

## MECHANICAL DATA

### TO-220 3-pin plastic flange-mount package

This single-in-line package consists of a circuit mounted on a lead frame and encapsulated within a plastic compound. The compound will withstand soldering temperature with no deformation, and circuit performance characteristics will remain stable when operated in high humidity conditions. Leads require no additional cleaning or processing when used in soldered assembly.



- NOTES: A. The centre pin is in electrical contact with the mounting tab.  
 B. Mounting tab corner profile according to package version.  
 C. Typical fixing hole centre stand off height according to package version.  
 Version 1, 18.0 mm. Version 2, 17.6 mm.

MDXXBE

## PRODUCT INFORMATION



# **TIC106 SERIES SILICON CONTROLLED RECTIFIERS**

APRIL 1971 - REVISED MARCH 1997

---

## **IMPORTANT NOTICE**

Power Innovations Limited (PI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to verify, before placing orders, that the information being relied on is current.

PI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with PI's standard warranty. Testing and other quality control techniques are utilized to the extent PI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except as mandated by government requirements.

PI accepts no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor is any license, either express or implied, granted under any patent right, copyright, design right, or other intellectual property right of PI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

PI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS.

Copyright © 1997, Power Innovations Limited

**PRODUCT INFORMATION**